



Sales Office:
 Engineered Synthetic Products, Inc.
 Phone (770) 564-1857
 Fax (770) 564-1818
 www.espgeosynthetics.com

Geotextile Product Description Sheet

SKAPS W106

SKAPS W106 is a woven monofilament material to be used for silt fence. Produced from first quality raw materials, they provide the perfect balance of strength and separation in styles capable of functioning exceptionally well in a wide range of performance requirements. Unless indicated below, all listed properties are Minimum Average Roll Values:

PROPERTY	TEST METHOD	UNIT	M.A.R.V. (Minimum Average Roll Value)
MD x TD Grab Tensile	ASTM D 4632	lbs	200 x 150
MD x TD Grab Elongation	ASTM D 4632	%	15 x 15
Mullen Burst Strength	ASTM D 3786	Psi	400
Permittivity	ASTM D 4491	l/sec (gpm/sf)	1.0 (100)
AOS	ASTM D 4751	US Sieve	30

PACKAGING	
Roll Dimensions (W x L) – ft	3' x 300'
Square Yards Per Roll	100
Estimated Roll Weight - lbs	50

This information is provided for reference purposes only and is not intended as a warranty or guarantee. SKAPS assumes no liability in connection with the use of this information.

SKAPS Industries, 316 S. Holland Dr., Pendergrass, GA 30567, Phone (706) 693-3440, Fax (706) 693-3450, Email: info@skaps.com

Made in U.S.A.